Data Sheet JDW-10

Article number: H530997

Differential pressure switch, 400...1600 Pa, internal setting

Differential pressure switch for monitoring overpressure, differential pressure or negative pressure of air and non-flammable, non-aggressive gases. Can be used as a fume cupboard or fan monitor or flow monitor to protect electrical heating registers, as a filter monitor, low air pressure protection or limit value controller. Note: Once the differential pressure switch has switched a voltage > 24 V and a current > 0.1 A, the gold coating on the contacts is burnt off. After this, the differential pressure switch can only be operated with this or a higher power. Note: The JZ-06/1 hose set is not included in the scope of delivery and must be ordered separately. Supplied without mounting bracket, can be screwed on directly (with 2 screws).

Number of outputs	2
Number of control ranges	1
Output signal	switching
External setting	No
Operation	internal setpoint adjuster
Pressure connection	6.2 mm
Electric connection	screw terminals
Electronic version	No
With explosion protection	No

ALRE-IT Regeltechnik GmbH
Richard-Tauber-Damm 10
D-12277 Berlin
Telefon: +49 30 399 84-0 **Telefax:** +49 30 391 70 05 **E-Mail:** mail@alre.de www.alre.de

Colour	black
Sensor element	pressure membrane
Function type (systems engineering)	monitor
Internal setting	Yes
Bearing temperature	15 … 80 °C
Max. air humidity (non-condensing)	95 % r.H.
Housing material	plastic
Max. Pressure	5000 Pa
Max. switching voltage	230 VAC, 50 Hz / 24 VDC
Max. switching current	1,5 (0,4) A (230 VAC), (1) (24 VAC), 0,2 A (30 VDC)
Medium	Air
Medium temperature	-15 … 80 °C
Min. switching voltage	12 VAC, 50 Hz / 12 VDC
Min. switching current	1 mA
Mounting/attachment	wall mounting
Surface finish	matt
Pressure control range	400 … 1600 Pa
Control function, overpressure or underpressure	Yes
Switching differential	60 … 30 Pa
Switching element	microswitch
Switching contact	two-way contact
Potential free switching contact	Yes

ALRE-IT Regeltechnik GmbH
Richard-Tauber-Damm 10
D-12277 Berlin
Telefon: +49 30 399 84-0 **Telefax:** +49 30 391 70 05 **E-Mail:** mail@alre.de www.alre.de

Protection class	IP54
Protection class	II, following appropriate mounting
Safety and EMC	in accordance with DIN EN 60730
Ambient temperature	-15 … 80 °C
Degree of contamination	2





ALRE-IT Regeltechnik GmbH
Richard-Tauber-Damm 10
D-12277 Berlin
Telefon: +49 30 399 84-0 **Telefax:** +49 30 391 70 05 **E-Mail:** mail@alre.de www.alre.de