

Data Sheet KTRRB-052.244

Article number: DA420600

Room thermostat for chilled ceilings, surface-mounted, 24 VAC/VDC, 2-/4-pipe

Electronic surface-mounted climate controller for heating/cooling control in 2- and 4-pipe systems for hotel, residential and commercial premises. Up to 5 valve actuators (24V~, normally closed or normally open) can be controlled per output. Particularly suitable for cooling ceiling control due to the possibility of dew point monitoring via optional external dew point sensors. To compensate for the inertia of controlled systems with cooling ceilings, the device has a temperature sensor input for connecting an external radiation sensor (optional). The external sensor can also be designed as a room sensor (optional) as an official variant where the controller should be inaccessible to unauthorized persons. An internal potentiometer can be used to select the use of the internal or external sensor or the use of both sensors with an adjustable weighting. Contact inputs for ECO function and OFF (frost protection).



Number of outputs	2
Number of outputs, heating	1
Number of outputs, cooling	1
Actual temperature display	No
Temperature controller version	climate controller
Output signal	switching
External setting	Yes
Operation	rotary knob

Operating voltage	24 VAC, 50 Hz / 24 VDC
Design	Berlin 2000
Display	No
ECO input (reduction)	24 VAC, 50 Hz / 24 VDC
ECO function (reduction)	Yes
Electric connection	screw terminals
Electronic control	Yes
Energy efficiency class	I
Colour	pure white
RAL colour number (similar)	9010
Sensor element	NTC internal, optional NTC external
Bearing temperature	-20 ... 70 °C
Max. air humidity (non-condensing)	95 % r.H.
Housing material	plastic ABS
Max. switching voltage	24 VAC, 50 Hz / 24 VDC
Max. switching current	1 A
Mechanical range reduction	Yes
Min. switching voltage	24 VAC, 50 Hz / 24 VDC
With receiver	No
Mounting/attachment	surface mounting
Neutral zone	2 K
Surface finish	matt

Control range	13 ... 29 °C
Heating control function	Yes
Cooling control function	Yes
Control behaviour	2-point
Switching differential	Heating/cooling: 1 K
Switching difference, can be adjusted	No
Switching element	2 relays
Switch Off/Comfort/ECO	No
On/Off switch	No
Heating/cooling switch	No
Additional heating switch	No
Switch/lamp night-time reduction	No
Switching contact	2 normally open contacts
Potential free switching contact	No
Switching power	24 W
Protection class	IP30
Protection class	III
Safety and EMC	in accordance with DIN EN 60730
Scale	Threshold arrows with "+" and "-"
Ambient temperature	0 ... 40 °C
Type of wiring	other
Degree of contamination	2

Assembly

complete device

Dimensions (W x H x D)

78,3 mm x 83,4 mm x 25,5 mm

