

## Data Sheet JTU-20

Article number: E6100075

Duct thermostat, 20...100 °C, external reset, capillary length 1250 mm

Minimum or maximum thermostat for supply air monitoring and fan control in ventilation and air conditioning systems. Overheating protection thermostat for electric heating coils and direct-fired air heaters in oil and gas operation.



Number of outputs	2
Number of control ranges	1
Output signal	switching/locking
External reset	Yes
Operation	internal setpoint adjuster, reset button
Rated impulse voltage	4000 V
Electric connection	screw terminals
Electronic control	No
With explosion protection	No
Colour	grey
Sensor element	capillary tube

Function type (systems engineering)	STB
Device version	surface-mounted unit
Internal setting	Yes
Bearing temperature	-15 ... 80 °C
Length of sensor	1250 mm
Capillary length	1.25 m
Max. air humidity (non-condensing)	95 % r.H.
Sensor material	Cu
Housing material	Metal sheet steel
Max. Sensor temperature	200 °C
Max. switching voltage	230 VAC, 50 Hz
Max. switching current	15 (8) A
Medium	Air
Min. switching voltage	24 VAC, 50 Hz
Min. switching current	150 mA
Mounting/attachment	mounting on air duct
Surface finish	matt
Burner control range	20 ... 100 °C
Heating control function	Yes
Cooling control function	Yes
Switching element	microswitch
Switching contact	two-way contact

Potential free switching contact	Yes
Switching power	3450 W
Protection class	IP40
Protection class	I
Safety and EMC	in accordance with DIN EN 60730
Scale	Degree Celsius
Ambient temperature	-15 ... 80 °C
Degree of contamination	2
Dimensions (W x H x D)	83 mm x 139 mm x 58 mm

